

LCD All-In-One type DVR Specifications



- LCD-All-in-one DVR system
- Easy to use
- Easy to complete camera line connection

SDVS		L4120MN
Operation system		• RTOS in Firmware
LCD Part	Resolution	• 1,024 * RGB * 768
	Pixel Pitch	• 0.97mm * 0.97mm
	NO. of Color	• 16,700,000 colors
	Luminance	• 250cd/m ²
	Contrast Ratio	• 300 : 1
DVR Part Specification		
Video Input Format		• NTSC/ PAL
Video In / Output CH		• 4/ 2 CH BNC (external connection Box support)
Sensor In/ Alarm Out CH		• 4/ 1 CH (external connection Box support)
Audio In/ Out CH		• 4/ 1 CH (external connection Box support)
Display Frame	NTSC	• 120 frames / sec
	PAL	• 100 frames/ sec
Recording Frame(Quad)	NTSC	• Max 30 fps (Quad)
	PAL	• Max 25 fps (Quad)
Recording frame(Each)	NTSC	• Max 7.5 fps (Each mode) Each mode = MAX fame / Number of video source
	PAL	• Max 6.25 fps Each mode = Max frame/ Number of video source
Resolution	Display	• NTSC : 720 X 480 • PAL : 720 X 576
	Recording	• NTSC : 320 X 112, 640 X 224 • PAL : 320 X 163, 640 X 272
Recording Mode		• Continuous, Manual, Event, Programmed, Software motion detection
Compression format		• Modified MJPEG(Encoding in DVR) • MPEG4(Via Network transmission)
Back up		• USB, Via Network(Remote playback)
Client requirement Specification		
CPU		• Pentium 4 – 1.4Ghz higher
Operating System		• Windows 2000 or XP
Main board chipset		• Intel chipset
RAM		• 128 MB
HDD		• Through USB port or External CD-RW(USB type), Remote S/W